# Lubrication Systems

www.aluratrailer.com sales@aluratrailer.com Export: +905442420491

## TRANSFER PUMP / OIL

RAASM / ITALY

| | | |
|---|---|---|
| Flow rate | 40 | l/min |
| Average air consumption | 370 | l/min |
| Ratio | 1:1 | |
| Compatible fluids | oils, lubricants and similar | |
| Suction tube upper body | aluminum | |
| Suction tube | carbon steel | |
| Air working pressure | 6 ÷ 8 | bar |
| Noise level | 81 | dB |
| max deliverable oil viscosity | 130 | SAE |
| Suitable for drums or tanks | 180 ÷ 220 | Kg |
| Weight | 7,3 | kg |

## HOSE

RAASM / ITALY

R1 1” Hose 7 mt.

## TRANSFER PUMP /COOLANT

RAASM / ITALY

| | | |
|---|---|---|
| Flow rate | 40 | l/min |
| Average air consumption | 370 | l/min |
| Ratio | 1:1 | |
| Compatible fluids | coolant,antifreeze,water | |
| Suction tube upper body | aluminum | |
| Suction tube | carbon steel | |
| Air working pressure | 6 ÷ 8 | bar |
| Noise level | 81 | dB |
| max deliverable oil viscosity | 130 | SAE |
| Suitable for drums or tanks | 180 ÷ 220 | Kg |
| Weight | 7,3 | kg |

## HOSE

RAASM / ITALY

R1 1” Hose 7 mt.