



























No	Equipment	Explanation	Orjin	Piece
1	Bodywork 5.70 x 2.45 x 2.20 mt	   <p>MWS Insulated Body Production from twisted C type channel steel. Base crosses 80mm height 3mm 18 mm Elastomeric rubber insulation walls. Floor 18mm Plywood plywood. Sliding windows into usable areas. Generator and compressor areas are quickly accessible. Exhaust and ventilation device. Stainless hinges and locks. Outdoor transportation center control board. Electrical cables are hidden inside the insulated chassis. Quick access cover to the lubricating and flushing cylinders. Solid crane connection channel to the body frame. Environmental and interior lighting 220 / 380W. Acrylic industrial chassis and surface paint. Quick access rear bumper drawers. Metal parts are fixed to the case. Side opening doors and working area 2 pcs.</p>	Alura Turkey	1
2	Generator Diesel	 <p>Standby/Prime Power: 22 kVa / 20 kVa Standard Voltage: 400/230 V / 3 Phase Engine Bran: Perkins Engine Model: 1103A-33TG1 Alternator: Sincron RPM: 1500 rpm. Frequency: 60 Hz. Water Cooling</p>	Power Turkey	1
3	Piston Compressor	 <p>Working Voltage : 380 V Pressure : 8 bar Air Tank : 530 lt Engine Power : 7.5 hp Air Suction : 920 lt/min Revolution : 1120 rpm</p>	Akomp Turkey	1
4	Water Transfer Set	 <p>Motor power : 1000 W Water Flow : 4500 l/hour Pressure : 50/5 m/bar Working pattern : 1.9 - 3 bar Maximum suction : 8 mt. Weight without accessories : 14.7 kg Dimensions (L x W x H) : 506 x 270 x 5 mm</p>	Karcher Germany	1







No	Equipment	Explanation	Orjin	Piece
5	Lubrication Oil Set	   <p> Pneumatic pumps for oil Flow rate: 18 l / min Air inlet - Fluid Out connection: G 1/4 - G 1/2 Air working pressure: 6/8 bar Average air consumption: 230 l / min Noise level: 81 dB Oil viscosity: 80 SAE Drum Hose Reels Pressure: 150 bar Compatible fluids: Oils and Similar Material: Painted Steel Inlet-Outlet : G 1/2 ""f - G 1/2 ""m Operating temperature: -40 / +100 Pressure - Size: 1/2 "" - 160 bar Length: 15 mt Guns for dispensing Flu: Technopolymer Digital meter: Yes Inlet swivel joint: G 1/2 f Filter: Yes Level locking button: Yes </p>	Raasm Italy	4
6	Waste Oil Systems Set	   <p> Diaphragm Pumps Flow rate: 70 l / min Max pressure: 8 bar. Max cycles for minute: 400 cpm. Max working temperature: 100 ° C Noise level: 70 dB Air working pressure: 2/6 Bar Membranes: EPDM Drum Hose Reels Pressure: 150 bar. Compatible fluids: Oils Swivel joint: Zinc plated steel Seals: Polyurethane Characteristic: Fixed Material: Painted steel Inlet - Outlet: G 1/2 "(f) - G 1/2 "(f) Single row steel wire braid with high tensile strength High resistance to oil and wear Operating temperature -40C to +100 C Pressure: 160 bar Length: 15 mt </p>	Raasm Italy	1







No	Equipment	Explanation	Orjin	Piece
7	Lubrication Grease Set	 <p>Grease dispenser kit for drums external Ratio: 50:1 Flow rate: 1500 g/min For drums with internal: \varnothing 370/420 Compatible fluids: Greases, medium / high viscosity Air inlet - Fluid out connection: G1/4f - G3/8f Air working pressure: 6/8 bar Average air consumption: 330 l / min Noise level: 81 dB Weight: 4.6kg Grease guns Inlet swivel joint: single G 1/4 "(f) Grease coupler: special 4-jaw Hose Reels Pressure : 400 bar Compatible fluids : Grease \varnothing and hose length : 3/8 - 25 mt. Swivel joint : Zinc plated steel Seals : Polyurethane Characteristic : Fixed Material : Painted Steel Couplings : Zinc Plated Steel\varnothingand hose length Reel flow path : Zinc Pated Steel Internal drum width : 122 mm</p>	Raasm Italy	1
8	Pressure Regulator	 <p>Air Inlet: 1/2 inch Filter : 20U Working Pressure : 05-9.9 Atu Working temperature : 5-60 ° C Water Capacity : 80 MI Air Permeability : 2200Lt / Dk.</p>	Osaka Japan	1
9	Air Hose Reels Set	 <p>Pressure: 20 bar. Compatible fluids: Air Swivel joint: Zinc plated steel Seals: Polyurethane Characteristic: Fixed Material: Painted steel Inlet - Outlet: G 1/2 "(f) - G 1/2 "(f) Hose : 20 Air Gun Tire Inflator Gun</p>	Raasm Italy	1

No	Equipment	Explanation	Orjin	Piece
10	Water Hode Reels Set 	Pressure: 20 bar. Compatible fluids: Water Swivel joint: Zinc plated steel Seals: Polyurethane Characteristic: Fixed Material: Painted steel Inlet - Outlet: G 1/2 "(f) - G 3/4 "(f) Hose 25 mt. Working Pressure: 15 Bar Input : 1/2" Maximum Temperature : 50 °C Length : 300mm Pipe Type : Aluminum	Raasm Italy	1
11	Diesel Pump Set 	Measurement Accuracy: 0.5% Flow rate: 50 lt/min Power: 230 VAC Suction distances: 5 m (vertical), 50 m (horizontal) Pressing distances: 30 mt (vertical), 300 mt (horizontal) Counter : Calibration and total storage unit with six digit crystal liquid display Motor : Thermal protector, ventilated, 0.25 kW, Body : Made of steel, epoxy painted against corrosion Gun : Automatic fuel gun Pressure: 20 bar. Compatible fluids: Water Swivel joint: Zinc plated steel Seals: Polyurethane Characteristic: Fixed Material: Painted steel Inlet - Outlet: G 1"(f) - G 1"(f) Hose: 15 mt Prism stainless tank Capacity: 1000 lt.	Gespaso İspanya	1
12	Water Tank 	Capacity : 900 Ltr Made of Stainless Steel Level Indicator Filling tap Pump stabilizer 1" Discharging valve	Alura Turkey	1

No	Equipment	Explanation	Orjin	Piece
13	Water Tank 	Capacity : 600 Ltr Made of Stainless Steel Level Indicator Filling tap Pump stabilizer 1" Discharging valve	Alura Turkey	1
14	Pressure Washer/COLD 	Electric Cold Washing Machine Pressure: 200 bar Flow rate: 900 lt/hour Engine Power: 7.5 hp Voltage - Phase 380V-3 50 Hz Weight: 74 Spray gun Pressure: 200 bar. Compatible fluids: Water Swivel joint: Stainless Metal Characteristic: Fixed Material: Painted steel Inlet: G 3/8" (f) Output: G 3/8""(f) Hose Length: 20 mt.	Rottest Italy	1
15	Work Bench 	Width: 1.800 mm Depth: 700 mm Height: 2.000 mm Number of Drawers: 3 Drawer Carrying Capacity: 60 kg. Shelf Carrying Cap .: 80 kg. Socket 2 Pieces 25 mm MDF + Pvc on worktops Central locking system in drawers Electrostatic powder paint Standard 2 220V sockets in electrically connected workbenches"	Plastmer Turkey	1

No	Equipment	Explanation	Orjin	Piece
16	Industrial Cabinet 	Drawers: 8 Height Adjustable Shelves: 3 Width : 1010 mm Depth : 615 mm Height : 2.000 mm These are leaf door, heavy load cabinets. They are welded, stabşe 1.20 mm sheet constructions. Electrostatic powder coated. There are round edged, embedded stripe channel, eloxal aluminium lugs and there are plastic taps on the lug heads."	Plastmer Turkey	1
17	Electric Reel 	415 VAC 3 phase - 240 VAC 1 phase Auto Loopback Thermoplastic Cable 4 socket outlet 240 VAC 3 pcs 380 VAC 1 pcs Cable : 25 mt.	Zeca Italy	1
18	Barrel Lifting Sling 	Carrying Capacity: 500/1.000 kg Test Load: 2.000 mm Diameter-Length : 6.3/516 mm Max. Barrel Diameter : 690 mm Weight : 3.6 kg	BigLift Turkey	1
19	Chain Crane 	Capacity : 1 Ton Test Load: 1.5 Tons Load Chain / Hardware: 100/1 nM Load Chain : 6.3x19 Hand Pull Force: 308 N Net Weight: 12.4 kg. Dimensions: (a) 161mm (b) 161mm (c) 33mm (d) 295mm	Atlas Kore	1
20	Outdoor Lighting 	240 Watts: 5800 Lumens Long: 30 Cm Working life: 30,000 hours Standard: IP67	EAE Turkey	12

No	Equipment	Explanation	Orjin	Piece
21	Control panel of all equipment. 	System control board Compressor control Water pump Generator Lighting	Alura Turkey	1
22	Interior Lighting 	Body : Polycarbonate RAL 9003 body , Metal lock clip Diffuser: Polycarbonate opal cover Light Source: Mid Power LED Consumption Power: 28 W / 38 W / 55 W Input Voltage: 220-240V AC 50/60 Hz CRI: >80 IP Value: IP65 Usage: Surface Mounted	EAE Turkey	4
23	Spare Tire Apparatus 	Wrapped type product features Static painted With safety rope In truck and trailer models Easy to assemble Pipe type product features Static painted Easy to assemble Truck type.	Nevpa Turkey	1
24	Liquid Measuring Cup 	Capacity : 1 Lt Container tin plate material Material discharge spout LDPE (low density polyethylene) Height : 270mm Base LxW : 190 x 90 mm Weight : 0.26 kg	Raasm Italy	1
25	Flexible Funnel 	Product Type: Stainless Steel Funnel Material: 304 Stainless Steel Color: Silver Diameter: Approx 14.8cm Weight: Approx. 141 g	Raasm Italy	1
26	Waste oil tank 	Oil Capacity: 16 Lt. / 8 Lt. Material : Plastic	Raasm Italy	2

No	Equipment	Explanation	Orjin	Piece
27	Tool Bag 	Metal 5 Drawers	Izeltaş Turkey	1
28	Work Lamp 	220V DC, 8W light with fluorescent bulb Impact resistant polycarbonate tube Protected against condensation of water vapor in humid environments Dust and shock resistant Protective insulation: VDE 0710 / 3.69 With hanger hook 5m power cord	Wert Germany	1
29	Barrel Wrench Tipe I 	Tap Type: large and small Barrel Type : 216 / 60 / 35 liter tapped steel drum Material : brass (stainless)	Beta Germany	1
30	Barrel Wrench Tipe II 	Tool for tightening and opening large and small caps of tapped metal drums.	Beta Germany	1
31	Hydraulic & Pneumatic Jack 	Folding Arm Mobile Jack Lifting Capacity: 40/25 tons Min. Height: 180 mm Mak. Height: 273 mm Lifting Distance: 40 / 85-25 / 80 mm Weight: 58 kg	Gemsa Turkey	1
32	Jack Stand 	Capacity: 6 / 12 Ton. Lifting Height: 450 / 600 mm.	Atek Turkey	1

No	Equipment	Explanation	Orjin	Piece
----	-----------	-------------	-------	-------

33	Tool Cabinet With Wheel	Material : Made of sheet metal Paint : Electrostatic Number of drawers: 7 pcs. 5 Drawer Dimensions: 400 x 548 x 68 mm. 2 Drawer Dimensions: 400 x 548 x 143 mm.	Izeltaş Turkey	1
----	--------------------------------	---	-------------------	---



D/E Open Jaw Wrench Long Pattern: 6×7-8×9-10×11-12×13-14×15-16×17-18×19-20×22-21×23-24×26

Combination Wrench Long Pattern: 6-7-8-9-10-11-12-13-14-17-19-22

D/E Ring Wrench

6×7 – 8×9 – 10×11 – 12×13 – 14×15 – 16×17 – 18×19 – 20×22

Combination Wrench Long: 16 – 18

1/4" Six Point Socket Wrench Set six point : 4 – 5 – 6 – 7 – 8 – 9- 10 – 11 – 12 – 13

1/4" Ratchet Handle

1/4" Sliding T Handle

1/4" Extension Bar : 50-100mm

1/4" Universal Joint

1/2" Six Point Socket Wrench Set Six Point :10-11-12-13-14-15-16-17-18-19-21-22-23-24-26-27-28 -30-32

1/2" Ratchet Handle

1/2" Universal Joint

1/2" Sliding T Handle Adapter

1/2" Extension Bar : 125 – 250 mm

1/2" Hexagonal Bits Sockets : H5-H6-H7-H8-H10-H12-H14

1/2" Star Bits Socket : T20-T25-T27-T30-T40-T45-T50-T55-T60

Hex Key Wrench Set: 2-2.5-3-3.5-4-5-6-7-8-9-10-12

Screwdriver, Stubby, Flat : 6.5 × 25

Screwdriver, Stubby, Phillips: 6 × 25

Bits Set in Plastic Case: 25 mm

Hexkey Wrench Ballpoint Set : 2-2.5-3-4 -5-6-8-10

Flexible Magnet Holder: 500 gr

Tire Lever: 400mm

Hand Brush: 3 Rows

Combination Wrench With Ratchet: 10 – 13 – 17 – 19 4

1/2" Deep Socket Wrench,six points : 10 – 11 – 12 – 13 – 14 – 15 – 16 – 17 – 18 – 19 10

1/2" Impact Socket Wrench : 13-17-18-19-24

Torx Allen Key T type : T9-T10-T15-T20-T25-T27-T30-T40

Adjustable Jaw Wrench: 10"

Special Grip : 250 mm

Combination Pliers: 180 mm

Circlip Pliers,External,Flat : 180 mm

Circlip Pliers,External,Bent : 170 mm

Circlip Pliers,Internal,Flat : 180 mm

Circlip Pliers,Internal,Bent : 170 mm

Nose Pliers: 200 mm

Side Cutting Pliers: 160 mm

Opaque Screwdriver, Flat : 4×100-5×125-6×150-8×175

Opaque Screwdriver, Phillips : 4.5×80-6×100

T Type Hex Key Wrench : 3-4-5-6-7-8

Flat Cold Chisel : 150 mm

Center Punch: 5×120

Drift Punch: 5mm

Split Pin Punch : 5 mm